



## GOVERNMENT COLLEGE OF ENGINEERING, JALGAON

(An Autonomous Institute of Government of Maharashtra)

National Highway No.6, JALGAON – 425 002

Phone No.: 0257-2281522

Fax No.: 0257-2281319

Website : www.gcoej.ac.in

E-mail : princoej@rediffmail.com



Name of Examination : **Summer 2021** - (Preview)

Course Code & Course Name : **ME352 - Metrology and Quality control**

Generated At : **19-04-2022 12:57:07**

Maximum Marks : **60**

Duration : **3 Hrs**

[Edit](#) [Print](#) [View Answer Key](#) [Close](#) **Answer Key Submission Type:** Marking scheme with model answers and solutions of numerical

Instructions:

- All questions are compulsory.
- Illustrate your answer with suitable figures/sketches wherever necessary.
- Assume suitable additional data; if required.
- Use of logarithmic table, drawing instruments and non programmable calculators is allowed.
- Figures to the right indicate full marks.

1) Attempt **All** from following Sub-Questions.

- a) How are Slip Gauges manufactured? What care is to taken for Slip Gauges? [6]
- b) Define the following [6]
- Metrology
  - Legal Metrology
  - Dynamic Metrology

2) Attempt any **Two** from following Sub-Questions.

- a) Compare a Vernier Calliper and Micrometer with reference to i) Robustness ii) ease of reading iii) adaptability iv) protection from dirt and accidental damages v) adjustment for wear vi) accuracy [6]
- b) A slip Gauge set with 87 pieces, as under is available. [6]

Range	Steps (mm)	No. of Blocks
1.001 - 1.009	0.001	9
1.01 - 1.49	0.01	49
0.5 - 9.5	0.5	19
10 - 90	10	9
1.005	-	1

Build up the following dimensions with minimum number of slip gauges (i) 29.578 mm; (ii) 46.635.

- c) What is the Solex Pneumatic Gauge? discuss in detail. Also draw the neat Principle diagram of Solex Pneumatic Gauge. [6]

3) Attempt any **Two** from following Sub-Questions.

- a) Design the general type of Go & No-GO gauge for component having  $20H_7f_8$  fit . [6]
- Given
- $i$  (micron) =  $0.45 (D)^{1/3} + 0.001D$ .
  - upper deviation of shaft 'f' =  $-5.5 D^{0.41}$ .
  - 20 mm falls in the diameter of step of 18 mm to 30 mm.
  - IT7 = 16i
  - IT8 = 25i
  - Wear allowance 10% of gauge tolerance.

- b) Write short notes on [6]

- CMM
- Tomlinson Surface Meter
- Hundred % inspection Vs Sampling Inspection

- c) What are the different types of pitch errors, which may occur on threaded component? [6]

4) Attempt any **Two** from following Sub-Questions.

- a) Describe with the sketch ' Parkinson Gear tester'. State its importance in gear measurement. [6]

- b) Explain the following terms [6]

- Quality Control
- Quality Design
- Quality Conformance

- c) Write a short note on P - chart [6]

5) Attempt **All** from following Sub-Questions.

- a) Give the steps required to construct the  $\bar{X}$  chart and R charts. [6]

- b) In automobile filling process, 500 gms. of certain liquid was to be filled in bags. The permissible variation is  $\pm 5$  gms. For investigating the process capability, 05 bags were taken at random each batch for successive batches and results were plotted as follows: [6]

Batch	1	2	3	4	5	6	7	8	9	10
Mean in gms.	501	498	500	503	501	500	497	502	503	496
Range	3	4	2	4	3	5	4	2	6	4

Establish Control chart limit for  $\bar{X}$  and R charts. Plot the charts and interpret the meaning. Take  $A_2 = 0.58$ ,  $D_3 = 0$ ,  $D_4 = 2.11$ . Will process be able to meet the specifications?

---

Auto Generated by SsOES v6.2

---